

Cat 5E F/PVC Cable



Kanberly Cable Code - **Cat 5 - KAN**

APPLICATION

A 4 pair high performance cable that consists of twisted pair conductors, used mainly for data transmission. Category 5E supports a frequency range of up to 100MHz and is designed for transmission speeds of up to 1 gigabit per second (Gigabit Ethernet).

CHARACTERISTICS

Temperature Rating

Fixed: -20°C to +70°C

Minimum Bending Radius

Fixed: 4 x overall diameter

Flexed: 8 x overall diameter

CONSTRUCTION

Conductor

Class 1 solid copper conductor

Insulation

HDPE (High Density Polyethylene)

Drain Wire

Tinned copper

Screen

Aluminium foil

Sheath

PVC (Polyvinyl Chloride)

Core Identification

Pair 1: ● Blue ● White/Blue

Pair 2: ● Orange ● White/Orange

Pair 3: ● Green ● White/Green

Pair 4: ● Brown ● White/Brown

Sheath Colour

● Grey ● Yellow ● Blue ● Green

CABLE ACCREDITATION



Cables are designed and confirmed by body like BASEC and ISI

STANDARDS

IEC 1801, TIA 568C.2

Flame Retardant according to IEC/EN 60332-1-2



THE CABLE LAB

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-team emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable

operations at: www.kanberycable.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable is compliant with European regulation EN 50575 and Bureau of Indian Standards, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab as meeting the requirements of the BSI RoHS Trusted Kitemark™.



DIMENSIONS

NO. OF PAIRS (24 AWG)	NOMINAL DIAMETER OVER INSULATION mm	NOMINAL OVERALL DIAMETER mm
4	1	6.2

PERFORMANCE CHARACTERISTICS

FREQUENCY MHz	ATTENUATION dB/100m	NEXT dB	PS-NEXT dB	RL dB	ELFEXT dB	PS-ELFEXT dB/100m	PHASE DELAY ns
1	2	65.3	62.3	20	63.8	60.8	570
4	4.1	56.3	53.3	23	51.8	48.8	552
8	5.8	51.8	48.8	24.5	45.7	42.7	546.73
10	6.5	50.3	47.3	25	43.8	40.8	545.38
16	8.2	47.2	44.4	25	39.7	36.7	543
20	9.3	45.8	42.8	25	37.8	34.8	542.05
25	10.4	44.3	41.3	24.3	35.8	32.8	541.2
31.25	11.7	42.9	39.9	23.6	33.9	30.9	540.44
62.5	17	38.4	35.4	21.5	27.9	24.9	538.55
100	22	35.3	32.3	20.1	23.8	20.8	537.6

ELECTRICAL CHARACTERISTICS

IMPEDANCE (1-100MHz) ohms	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km	MAXIMUM RESISTANCE UNBALANCE %
100±15	6.2	14

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.