

POLYWRAP SUBMERSIBLE MOTOR WINDING WIRE



Kanbery Cable Code - **POLYWRAP WINDING-KAN**

APPLICATIONS

Kanbery's specially designed Submersible Copper Winding wire is wrapped with thin polyester film and Biaxial Oriented Polypropylene (BOPP) film. It offers the highest quality for submersible motors, ensuring trouble-free operation and long life. These wires serve a maximum range of submersible pump manufacturers and thousands of rewinders across the country.

CHARACTERISTICS

Voltage Rating

Up to and including 1100V
Tested with 3500V

Temperature Rating

Fixed : -20°C to +90°C

Minimum Bending Radius

Fixed: 6 x overall diameter

CONSTRUCTION

Conductor

99.98% Pure Electrolyte grade bright Annealed bare copper conductor use as per IEC 60228

Insulation

Specially formulated with colour (BOPP)
(Biaxially oriented polypropylene) tapp use for Insulation

Insulation for Use

- Do not stack more than 4 coils otherwise, bottom coil is likely to get damaged due to upper coil weight.
- Always keep away winding wire from those things having sharp edges and equipment generate heat to avoid unintentional damage. Also avoid welding spark falling on winding.
- Motor manufacturers must ensure proper cable joining after winding to avoid megger or winding failer.

STANDARDS

IEC : 60228

IEC 60332

THE CABLE LAB

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable

operations at: www.kanberycable.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable is compliant with European regulation EN 50575 and Bureau of Indian Standards, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab as meeting the requirements of the BSI RoHS Trusted Kitemark™.



DIMENSIONS

| Sr. No. | Nominal Conductor Diameter / mm | Conductor Cross Sectional Area Nominal / mm | Appx.Overall Diameter / mm | Max. D.C Conductor Resistance / ohm / km | Elongation (min.) % | Appx. Weight Per 1000m / kg. |
|---------|---------------------------------|---|----------------------------|--|---------------------|------------------------------|
| 01 | 0.40 | 0.126 | 0.80 | 140 | 24 | 1.47 |
| 02 | 0.50 | 0.196 | 0.90 | 89.6 | 25 | 2.15 |
| 03 | 0.60 | 0.283 | 1.00 | 62.2 | 26 | 2.98 |
| 04 | 0.70 | 0.385 | 1.10 | 45.7 | 28 | 3.95 |
| 05 | 0.80 | 0.502 | 1.20 | * 35 | 28 | 5.05 |
| 06 | 0.90 | 0.636 | 1.30 | 27.6 | 29 | 6.30 |
| 07 | 1.00 | 0.785 | 1.40 | 22.4 | 30 | 7.80 |
| 08 | 1.10 | 0.95 | 1.50 | 18.5 | 30 | 9.20 |
| 09 | 1.20 | 1.13 | 1.60 | 15.5 | 31 | 10.90 |
| 10 | 1.30 | 1.33 | 1.70 | 13.2 | 32 | 12.70 |
| 11 | 1.40 | 1.54 | 1.90 | 11.4 | 32 | 14.90 |
| 12 | 1.50 | 1.77 | 2.00 | 9.95 | 32 | 17.00 |
| 13 | 1.60 | 2.01 | 2.10 | 8.75 | 32 | 19.20 |
| 14 | 1.70 | 2.27 | 2.20 | 7.75 | 32 | 21.60 |
| 15 | 1.80 | 2.54 | 2.30 | 6.91 | 32 | 24.20 |
| 16 | 1.90 | 2.83 | 2.40 | 6.2 | 32 | 26.80 |
| 17 | 2.00 | 3.14 | 2.50 | 5.6 | 33 | 29.60 |
| 18 | 2.10 | 3.46 | 2.60 | 5.08 | 33 | 32.55 |
| 19 | 2.20 | 3.8 | 2.70 | 4.63 | 33 | 35.60 |
| 20 | 2.30 | 4.15 | 2.80 | 4.23 | 33 | 38.85 |
| 21 | 2.40 | 4.52 | 2.90 | 3.89 | 33 | 42.20 |
| 22 | 2.50 | 4.91 | 3.00 | 3.58 | 33 | 45.70 |
| 23 | 2.60 | 5.31 | 3.10 | 3.31 | 34 | 49.30 |
| 24 | 2.70 | 5.73 | 3.20 | 3.07 | 34 | 53.10 |
| 25 | 2.80 | 6.16 | 3.30 | 2.86 | 34 | 57.00 |
| 26 | 2.90 | 6.61 | 3.40 | 2.66 | 34 | 61.05 |
| 27 | 3.00 | 7.07 | 3.50 | 2.49 | 34 | 65.25 |